



Securing Today for a Profitable Tomorrow

# Stealth Pad™

## 58KHz Distance Deactivator

Stealth Pad Distance Deactivator is a very compact unit designed for minimal counter space. It Provides excellent deactivation reliability and high throughput.

The Stealth Pad Antenna is configured for table-top operation but can also be set flush mount to the counter-top in a mounting tray. Tuning is easily accomplished via the handheld IR remote, providing complete control with password protection.



**Compatible with all 58KHz Acousto-Magnetic Labels**

### Proximity Deactivation

With up to 10cm (4") distance deactivation, Stealth Pad is an excellent product for both source and retailer tagged merchandise

### Compact Size

Designed to fit where counter space is at a premium. The small antenna footprint allows it to be easily placed on the countertop or flush mount.

### Audible/Visual Notification

Stealth Pad includes both audible and visual notification for efficient and reliable operation

### IR Remote Controller

Stealth Pad is easily tuned with a convenient hand held IR remote control.

### Password Protected

Individual product security is facilitated with a changeable password

### Transmitter

Operating Frequency: 58KHz  
Transmit Burst Duration: 1.6ms  
Current: 3A Peak (Nominal)

### Regulatory

CE, FCC, UL

### Physical

Antenna: (LxWxD) 159x178x76mm (6.25"x7"x3")  
Weight: 8.5 kg (19lb)  
Control Box: (LxWxD) 275x190x140mm (10.8"x7.5"x5.5")  
Weight: 3 kg (6.6 lb)  
Mounting Tray: (LxWxD) 203x235x89mm (8"x9.25"x3.5")  
Weight: 0.24 kg (0.53 lb)

### Electrical

Voltage: 100/120vac, 60Hz  
220/240vac, 50Hz  
Current Draw: 6A max @240vac

### Environmental

Operating Temperature: 0-49°C (32-120°F)  
Relative Humidity: 0-85% Non-condensing

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE